


SOT-23 贴片塑封肖特基二极管

SOT-23 Plastic-Encapsulate Schottky Barrier Diode



特征 Features

- 大电流承受能力。High Current Capability
- 正向压降低。Low Forward Voltage Drop
- 开关速度快。Extremely Fast Switching Speed

机械数据 Mechanical Data

- 封装: SOT-23 封装 SOT-23 Small Outline Plastic Package
- 环氧树脂UL易燃等级Eproxy UL:94V-0
- 安装位置: 任意 Mounting Position: Any
- Device meets MSL 1 requirements

极限值和温度特性($T_A = 25^\circ\text{C}$ 除非另有规定)





Maximum Ratings & Thermal Characteristics ($T_A=25^\circ\text{C}$ unless otherwise specified)

参数 Parameters	符号 Symbol	数值 Value	单位 Unit
最大可重复峰值反向电压 Maximum repetitive peak reverse voltage	V_{RRM}	30	V
最大均方根电压 Maximum RMS voltage	V_{RMS}	21	V
最大直流阻断电压 Maximum DC blocking voltage	V_{DC}	30	V
最大正向平均整流电流 Maximum average forward rectified current	I_{FM}	200	mA
峰值正向浪涌电流8.3ms单一正弦半波 Peak forward surge current 8.3 ms single half sine-wave	I_{FSM}	600	mA
典型热阻 Typical thermal resistance	$R_{\theta JA}$	500	$^\circ\text{C}/\text{W}$
功率消耗 Power Dissipation	PD	200	mW
结温 Junction Temperature	T_j	125	$^\circ\text{C}$
存储温度 Storage temperature range	T_{stg}	-50-+150	$^\circ\text{C}$


电特性 Electrical Characteristics($T_A=25^\circ\text{C}$ unless otherwise specified)

参数 Parameter	符号 Symbols	测试条件 Test Condition	界限 Limits		单位 Unit
			Min	Max	
正向电压 Forward Voltage	V_F	$I_F=0.1\text{mA}$	---	0.24	V
		$I_F=1.0\text{mA}$	---	0.32	V
		$I_F=10\text{mA}$	---	0.40	V
		$I_F=30\text{mA}$	---	0.50	V
		$I_F=100\text{mA}$	---	1.0	V
反向电压 Reverse breakdown voltage	V_R	$I_R=100\mu\text{A}$	30	---	V
反向电流 Reverse current	I_R	$V_R=25\text{V}$	---	2.0	μA
典型结电容 Type junction capacitance	C_J	$V_R=0\text{V}, f=1\text{MHz}$	---	10	pF
反向恢复时间 Reverse Recovery time	t_{rr}	$I_F=I_R=10\text{mA}$ $I_{rr}=0.1I_{IR}, R_L=100\Omega$		5	nS


Typical Performance Characteristics ($T_A=25^\circ\text{C}$ unless otherwise Specified)



SOT-23 Package Outline Drawing



Suggested Land Pattern



Note:


1. Controlling dimension: In millimeters.
2. General tolerance: ± 0.05 mm.
3. The pad layout is for reference purposes only.

Ordering Information



Part Number	Shipping	Reel Size
BAT54A	3000/Tape & Reel	7 inch

TAPE AND REEL INFORMATION

Reel Dimensions



Tape Dimensions



→
User Direction of Feed

IMPORTANT NOTICE

The information given in this document is believed to be accurate and reliable but shall in no event be regarded as a guarantee of conditions or characteristics. PN-Silicon assumes no responsibility for any errors in this document, or for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of PN-Silicon.

The product listed in this document are designed to be used with ordinary electronic equipment or devices and are not authorized to used with equipment or devices which require an extremely high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, aerospace machinery, nuclear-reactor controllers, automotive and other safety device.)

The  logo is a registered trademark of PN-Silicon co., ltd which reserves the right to make changes to the product or this document at any time without notice. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. PN-Silicon makes no warranty, representation or guarantee, express or implied, regarding the suitability of its products for any particular purpose. All rights reserved.