

30V 50A N-Channel MOSFET

MOSFET Product Summary

V_{DS}	$R_{DS(ON)}$ (Typ.)	I_D
30V	4.4mΩ @ $V_{GS}=10V$	50A
	7.3mΩ @ $V_{GS}=4.5V$	


Description

The PM03N30D338 uses advanced Trench technology and designs to provide excellent $R_{DS(ON)}$ with low gate charge. It can be used in a wide variety of applications. The package form is PDFN3.3*3.3-8L, with the RoHS standard and Halogen Free standard.


Features

- Low Gate Charge and $R_{DS(ON)}$
- Lead free product is acquired
- High Power and current handing capability

Dimensions and Pin Configuration



Circuit diagram



Bottom View


Mechanical Characteristics

- Package: PDFN3.3*3.3-8L
- Case Material: "Green" Molding Compound
- Marking Information: See Below

Applications

- DC-DC converter
- Load Switch
- Power Management
- Apply for high-frequency switching and synchronous rectification

Marking Information



3030 = Device Marking Code

Ordering Information

Part Number	Shipping	Reel Size
PM03N30D338	5000/Tape & Reel	13 inch

Absolute Maximum Ratings ($T_A=25^{\circ}C$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	30	V
Gate-Source Voltage	V_{GS}	±20	V
Continuous Drain Current ^(Note1)	I_D	50	A
Pulsed Drain Current ^(Note2)	I_{DM}	195	A

Power Dissipation ^(Note4)	P_D	6.25	W
Thermal Resistance from Junction to Ambient ^(Note3)	$R_{\theta JA}$	45	°C/W
Junction Temperature	T_J	-55~ +150	°C
Storage Temperature	T_{STG}	-55~ +150	°C


Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-to-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250μA	30	-	-	V
Zero Gate voltage Drain Current	I _{DSS}	V _{DS} =30V, V _{GS} =0V	-	-	1	μA
Gate-to-Source Leakage Current	I _{GSS}	V _{GS} =±20V, V _{DS} =0V	-	-	±100	nA
Gate Threshold Voltage	V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250μA	1.0	1.6	2.0	V
Drain-to-Source On-Resistance	R _{DS(ON)}	V _{GS} =10V, I _D =20A	-	4.4	6	mΩ
		V _{GS} =4.5V, I _D =20A	-	7.3	9	
Diode Forward Voltage	V _{SD}	I _S =20A,V _{GS} =0V	-	0.83	1.25	V
Dynamic Characteristics						
Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Input Capacitance	C _{iss}	V _{GS} =0V, V _{DS} =15V, f=1MHz	-	1610	-	pF
Output Capacitance	C _{oss}		-	197	-	
Reverse Transfer Capacitance	C _{rss}		-	183	-	
Switching Characteristics						
Turn-On Delay Time	t _{d(on)}	V _{GS} =10V, V _{DS} =15V, R _L =0.75Ω, R _{GEN} =3Ω	-	12.8	-	nS
Turn-On Rise Time	t _r		-	7	-	
Turn-Off Delay Time	t _{d(off)}		-	48	-	
Turn-Off Fall Time	t _f		-	11.5	-	
Gate Total Charge	Q _g	V _{GS} =10V, V _{DS} =15V, I _D =15A	-	41.2	-	nC
Gate-Source Charge	Q _{gs}		-	6.5	-	
Gate-Drain Charge	Q _{gd}		-	12	-	


Notes:

1. This current is chip limited, which is calculated based on $R_{\theta JA}$.
2. This current is calculated on single pulse with 10 μs Pulse & Duty Cycle = 1%.
3. The value of $R_{\theta JA}$, which is steady state, is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, with $T_A=25^\circ\text{C}$.
4. The power dissipation is based on $R_{\theta JA}$ $t \leq 10s$ value and the $T_{J(MAX)}=150^\circ\text{C}$. The value in any given application is determined by the user's specific board design.


Typical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise specified)




Drain Current vs. Drain-Source Voltage




Drain Current vs. Gate-Source Voltage




$R_{DS(on)}$ On-Resistance vs. Drain-Current



Capacitance vs. Drain-Source Voltage




On-Resistance vs. Gate-Source Voltage




Threshold Voltage vs. Temperature

PDFN3.3*3.3-8L Package Outline Drawing




Symbol	Dimensions In Millimeters	
	Min.	Max.
A	-	0.90
b	0.25	0.40
C	0.15	0.25
D	3.05	3.25
D1	2.35	2.75
E	3.20	3.45
E1	2.90	3.20
E2	1.52	1.92
e	0.65BSC	
H1	0.31	0.52
H2	0.25	0.50
K	0.67	0.96
L1/L2	0.05	0.23
θ	8°	13°
N	0.00	0.15
O	0.2REF	

Suggested Land Pattern (Unit: mm)





TAPE AND REEL INFORMATION

Reel Dimensions



Tape Dimensions



User Direction of Feed

IMPORTANT NOTICE

The information given in this document is believed to be accurate and reliable but shall in no event be regarded as a guarantee of conditions or characteristics. PN-Silicon assumes no responsibility for any errors in this document, or for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of PN-Silicon.

The product listed in this document are designed to be used with ordinary electronic equipment or devices and are not authorized to used with equipment or devices which require an extremely high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, aerospace machinery, nuclear-reactor controllers, automotive and other safety device.)

The  logo is a registered trademark of PN-Silicon co., ltd which reserves the right to make changes to the product or this document at any time without notice. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. PN-Silicon makes no warranty, representation or guarantee, express or implied, regarding the suitability of its products for any particular purpose. All rights reserved.