

1-Line Ultra Low Capacitance Bi-directional TVS Diode


Description

The PESDR2011P0A is a bi-directional TVS diode, to provide fast response time and low ESD clamping voltage, making this device an ideal solution for protecting voltage sensitive high speed data lines. The PESDR2011P0A has an ultra-low capacitance with a typical value at 0.13pF, and complies with the IEC61000-4-2 (ESD) standard with $\pm 30\text{kV}$ air and $\pm 30\text{kV}$ contact discharge. It is assembled into an ultra-small 1.0x0.6x 0.5mm lead-free DFN package. The small size, ultra-low capacitance and high surge protection make PESDR2011P0A an ideal choice to protect cellphone, digital video interfaces and other high speed ports.


Features

- Ultra small package: 0.6x0.3x0.3mm
- Ultra low capacitance: 0.13pF typical
- Low operating voltage: 20 V
- Low clamping voltage
- 2-pin leadless package
- Complies with following standards:
 - IEC 61000-4-2 (ESD) immunity test
 - Air discharge: $\pm 30\text{kV}$
 - Contact discharge: $\pm 30\text{kV}$
 - IEC61000-4-5 (Lightning) 4.5A (8/20 μs)
- RoHS Compliant

Dimensions and Pin Configuration



Package Dimensions



Circuit and Pin Schematic

Mechanical Characteristics

- Package: DFN0603-2 (0.6x0.3x0.3mm)
- Case Material: "Green" Molding Compound.
- Moisture Sensitivity: Level 1 per J-STD-020
- Marking Information: See Below

Applications

- Cell phone handsets and accessories
- Personal digital assistants(PDA's)
- Notebooks,desktops,and servers
- Portable instrumentation
- Cordless phones
- Digital cameras
- Peripherals

Marking Information



PS = Device Marking Code

Ordering Information

Part Number	Shipping	Reel Size
PESDR2011P0A	10000/Tape & Reel	7 inch

Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20 μs)	P_{PK}	90	W
Peak Pulse Current (8/20 μs)	I_{PP}	4.5	A
ESD per IEC 61000-4-2 (Air)	V_{ESD}	± 30	kV
ESD per IEC 61000-4-2 (Contact)		± 30	
Lead temperature	T_L	260	$^{\circ}\text{C}$
Junction Temperature	T_J	125	$^{\circ}\text{C}$
Operating Temperature Range	T_{OP}	$-40 \sim +125$	$^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	$-55 \sim +150$	$^{\circ}\text{C}$

Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Reverse Working Voltage	V_{RWM}			20	V	
Breakdown Voltage	V_{BR}	21			V	$I_T = 1\text{mA}$
Reverse Leakage Current	I_R			0.2	μA	$V_{RWM} = 20\text{V}$
Holding Voltage	V_H	15			V	$I_H = 80\text{mA}$
Clamping voltage ¹⁾	V_{CL}		23		V	$I_{PP} = 16\text{A}$, $t_p = 100\text{ns}$
Dynamic resistance ¹⁾	R_{DYN}		0.5		Ω	
Clamping Voltage ²⁾	V_C		23		V	$V_{ESD} = 8\text{kV}$
Clamping Voltage ³⁾	V_C			21	V	$I_{PP} = 3\text{A}$ (8/20 μs pulse)
Clamping Voltage ³⁾	V_C			22	V	$I_{PP} = 4.5\text{A}$ (8/20 μs pulse)
Junction Capacitance	C_J		0.13	0.2	pF	$V_R = 0\text{V}$, $f = 1\text{MHz}$


Notes:

1) TLP parameter: $Z_0 = 50\Omega$, $t_p = 100\text{ns}$, $t_r = 2\text{ns}$, averaging window from 60ns to 80ns. R_{DYN} is calculated from 4A to 16A.

2) Contact discharge mode, according to IEC61000-4-2.


3) Non-repetitive current pulse, according to IEC61000-4-5.

Electrical characteristics ($T_A = 25^\circ\text{C}$, unless otherwise noted)




Definitions of electrical characteristics


Typical Performance Characteristics (TA=25°C unless otherwise Specified)




Junction Capacitance vs. Reverse Voltage




Peak Pulse Power vs. Pulse Time




Clamping Voltage vs. Peak Pulse Current



Power Derating Curve




8/20 μs Pulse Waveform




TLP Measurement

DFN0603-2 Package Outline Drawing



Symbol	Dimensions in Millimeters		
	Min.	Typ.	Max.
A	0.230	0.300	0.350
A1	0.000	-	0.050
A3	0.102REF.		
D	0.550	0.600	0.670
E	0.250	0.300	0.370
b	0.160	0.190	0.230
L	0.215	0.245	0.275
e	0.360 BSC		

Recommended PCB Layout (Unit: mm)




Notes:


This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met.

TAPE AND REEL INFORMATION


Reel Dimensions



Tape Dimensions



Unit:mm



→
User Direction of Feed

IMPORTANT NOTICE

The information given in this document is believed to be accurate and reliable but shall in no event be regarded as a guarantee of conditions or characteristics. PN-Silicon assumes no responsibility for any errors in this document, or for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of PN-Silicon.

The product listed in this document are designed to be used with ordinary electronic equipment or devices and are not authorized to used with equipment or devices which require an extremely high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, aerospace machinery, nuclear-reactor controllers, automotive and other safety device.)

The  logo is a registered trademark of PN-Silicon co., ltd which reserves the right to make changes to the product or this document at any time without notice. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. PN-Silicon makes no warranty, representation or guarantee, express or implied, regarding the suitability of its products for any particular purpose. All rights reserved.