

1-Line Uni-directional TVS Diode


Description

PESDU2401D5N is a Uni-directional Electro-Static Discharge (ESD) protection diode in a SOD523 plastic package. The PESDU2401D5N complies with the IEC 61000-4-2 (ESD) standard with $\pm 30\text{kV}$ air and $\pm 30\text{kV}$ contact discharge. It is designed to protect one transmission or data line from the damage caused by ESD and other transients.

Features

- Uni-directional ESD protection of one line
- Reverse stand-off voltage: 24V Max
- Low leakage current: nA level
- Response time is typically $< 1\text{ ns}$
- Complies with following standards:
 - IEC 61000-4-2 (ESD) immunity test
 - Air discharge: $\pm 30\text{kV}$
 - Contact discharge: $\pm 30\text{kV}$
 - IEC 61000-4-5 (Lightning) 6A ($8/20\mu\text{s}$)
- RoHS Compliant

Schematic and Pin Configuration



Graphic symbol

Mechanical Characteristics

- Package: SOD-523
- Case Material: "Green" Molding Compound.
- Moisture Sensitivity: Level 1 per J-STD-020
- Marking Information: See Below

Applications

- Cellular phones
- Portable devices
- Digital Cameras
- Power supplies

Marking Information



N5 = Device Marking Code

Bar denotes cathode

Ordering Information

Part Number	Shipping	Reel Size
PESDU2401D5N	3000/Tape & Reel	7 inch


Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20 μs)	P_{pk}	330	W
Peak Pulse Current (8/20 μs)	I_{PP}	6	A
ESD per IEC 61000-4-2 (Air)	V_{ESD}	± 30	kV
ESD per IEC 61000-4-2 (Contact)		± 30	
Lead temperature	T_L	260	$^{\circ}\text{C}$
Junction Temperature	T_J	125	$^{\circ}\text{C}$
Operating Temperature Range	T_{OP}	$-40 \sim +125$	$^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	$-55 \sim +150$	$^{\circ}\text{C}$

Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise specified)


Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Reverse Working Voltage	V_{RWM}			24	V	
Breakdown Voltage	V_{BR}	26			V	$I_T = 1\text{mA}$
Reverse Leakage Current	I_R			100	nA	$V_{RWM} = 24\text{V}$
Clamping Voltage	V_C			33	V	$I_{PP} = 1\text{A}$ (8/20 μs pulse)
Clamping Voltage	V_C			55	V	$I_{PP} = 6\text{A}$ (8/20 μs pulse)
Junction Capacitance	C_J		25		pF	$V_R = 0\text{V}$, $f = 1\text{MHz}$

Electrical characteristics ($T_A = 25^{\circ}\text{C}$, unless otherwise noted)




Definitions of electrical characteristics


Typical Performance Characteristics (T_A=25°C unless otherwise Specified)




Junction Capacitance vs. Reverse Voltage




Peak Pulse Power vs. Pulse Time



Clamping Voltage vs. Peak Pulse Current




Power Derating Curve




8/20μs Pulse Waveform

SOD523 Package Outline Drawing



SYM	DIMENSIONS			
	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	1.10	1.30	0.043	0.051
B	0.70	0.90	0.028	0.035
C	1.50	1.70	0.059	0.067
D	0.50	0.70	0.020	0.028
E	0.25	0.35	0.010	0.014
F	0.10	0.20	0.004	0.008
G	0.40	0.50	0.016	0.020


Suggested Land Pattern




SYM	DIMENSIONS	
	MILLIMETERS	INCHES
C	1.42	0.056
X	0.70	0.028
Y	0.60	0.024

TAPE AND REEL INFORMATION


Reel Dimensions



Tape Dimensions



Unit:mm



IMPORTANT NOTICE

The information given in this document is believed to be accurate and reliable but shall in no event be regarded as a guarantee of conditions or characteristics. PN-Silicon assumes no responsibility for any errors in this document, or for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of PN-Silicon.

The product listed in this document are designed to be used with ordinary electronic equipment or devices and are not authorized to used with equipment or devices which require an extremely high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, aerospace machinery, nuclear-reactor controllers, automotive and other safety device.)

The **PN SILICON** logo is a registered trademark of PN-Silicon co., ltd which reserves the right to make changes to the product or this document at any time without notice. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. PN-Silicon makes no warranty, representation or guarantee, express or implied, regarding the suitability of its products for any particular purpose. All rights reserved.