


SOT-23



1. BASE

2. EMITTER

3. COLLECTOR

MARKING:YW

特征 Features

- 与MMBTA43配对;Complementary to MMBTA43
- 最大功率耗散 350mW; Power Dissipation of 350mW
- 高稳定性和可靠性。High Stability and High Reliability

机械数据 Mechanical Data

- 封装: SOT-23 封装 SOT-23 Small Outline Plastic Package
- 环氧树脂UL 易燃等级Epoxy UL: 94V-0
- 安装位置: 任意 Mounting Position: Any
- Device meets MSL 1 requirements

极限值和温度特性(TA = 25℃ 除非另有规定)

Maximum Ratings & Thermal Characteristics (TA=25℃ unless otherwise specified)

参数 Parameters	符号 Symbol	数值 Value	单位 Unit
Collector-Base Voltage	VCBO	-200	V
Collector-Emitter Voltage	VCEO	-200	V
Emitter -Base Voltage	VEBO	-5	V
Collector Current-Continuous	IC	-500	mA
Collector Power Dissipation	PC	350	mW
Junction Temperature	Tj	150	℃
Storage Temperature	TSTG	-55-+150	℃
Thermal resistance from junction to ambient	RθJA	357	℃/W


电特性 Electrical Characteristics (TA=25℃ unless otherwise specified)

参数 Parameter	符号 Symbols	测试条件 Test Condition	界限 Limits		单位 Unit
			Min	Max	
Collector-base breakdown voltage	V(BR)CBO	IC=-100uA, IE=0	-200		V
Collector-emitter breakdown voltage	V(BR)CEO*	IC=-1mA, IB=0	-200		V
Emitter-base breakdown voltage	V(BR)EBO	IE=-100uA, IC=0	-5		V
Collector cut-off current	ICBO	VCB=-200V, IE=0		-250	nA
Collector cut-off current	ICEO	VCE=-200V, IB=0		-250	nA

Emitter cut-off current	I_{EBO}	$V_{EB}=-5V, I_C=0$		-100	nA
DC current gain	$hFE(1)^*$	$V_{CE}=-10V, I_C=-10mA$	40		
	$hFE(2)^*$	$V_{CE}=-10V, I_C=-1mA$	25		
	$hFE(3)^*$	$V_{CE}=-10V, I_C=-30mA$	25		
Collector-emitter saturation voltage	$V_{CE(sat)}^*$	$I_C=-20mA, I_B=-2mA$		-0.5	V
Base -emitter saturation voltage	$V_{BE(sat)}^*$	$I_C=-20mA, I_B=-2mA$		-0.9	V
Transition frequency	f_T	$V_{CE}=-20V, I_C=10mA, f=30MHz$	50		MHz
Collector output capacitance	C_{ob}	$V_{CB}=-20V, I_E=0, f=1MHz$		8	pF

*Pulse test: pulse width $\leq$ 300us, duty cycle $\leq$ 2.0%


SOT-23 Package Outline Drawing



SYMBOL	DIMENSIONS	
	MIN.	MAX.
A	0.900	1.150
A1	0.000	0.100
A2	0.900	1.050
b	0.300	0.500
c	0.080	0.150
D	2.800	3.000
E	1.200	1.400
E1	2.250	2.550
e	0.950TYP	
e1	1.800	2.000
L	0.550REF	
L1	0.300	0.500
θ	0°	8°

Unit: mm

Suggested Land Pattern



Note:


1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

Ordering Information



Part Number	Shipping	Reel Size
MMBTA93	3000/Tape & Reel	7 inch

Tape and Reel Information

Reel Dimensions



Tape Dimensions



User Direction of Feed

IMPORTANT NOTICE

The information given in this document is believed to be accurate and reliable but shall in no event be regarded as a guarantee of conditions or characteristics. PN-Silicon assumes no responsibility for any errors in this document, or for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of PN-Silicon.

The product listed in this document are designed to be used with ordinary electronic equipment or devices and are not authorized to used with equipment or devices which require an extremely high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, aerospace machinery, nuclear-reactor controllers, automotive and other safety device.)

The  logo is a registered trademark of PN-Silicon co., ltd which reserves the right to make changes to the product or this document at any time without notice. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. PN-Silicon makes no warranty, representation or guarantee, express or implied, regarding the suitability of its products for any particular purpose. All rights reserved.