

-16V P-Channel MOSFET

MOSFET Product Summary

V_{DS}	$R_{DS(ON)}(Typ.)$	I_D
-16V	27m Ω @ $V_{GS}=-4.5V$	-6A
	38m Ω @ $V_{GS}=-2.5V$	


Description

The PM2305AL3 uses advanced Trench technology and designs to provide excellent $R_{DS(ON)}$ with low gate charge. It can be used in a wide variety of applications. The package form is SOT23-3L, which accord with the RoHS standard and Halogen Free standard.


Features

- Low Gate Charge and $R_{DS(ON)}$
- Lead free product is acquired
- High Power and current handling capability

Dimensions and Pin Configuration



Circuit diagram



SOT23-3L


Mechanical Characteristics

- Package: SOT23-3L
- Case Material: "Green" Molding Compound
- Marking Information: See Below

Applications

- DC-DC converter
- Apply for high-frequency switching and synchronous rectification

Marking Information



2305A3 = Device Marking Code

Ordering Information

Part Number	Shipping	Reel Size
PM2305AL3	3000/Tape & Reel	7 inch

Absolute Maximum Ratings ($T_A=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	-16	V
Gate-Source Voltage	V_{GS}	± 12	V
Continuous Drain Current	I_D	-6	A

Pulsed Drain Current _(note1)	I_{DM}	-22.4	A
Power Dissipation	P_D	1.6	W
Thermal Resistance from Junction to Ambient _(note1)	$R_{\theta JA}$	80	°C/W
Junction Temperature	T_J	-55~ +150	°C
Storage Temperature	T_{STG}	-55~ +150	°C


Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-source breakdown voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D =-250μA	-16	-	-	V
Zero gate voltage drain current	I _{DSS}	V _{DS} =-16V, V _{GS} = 0V	-	-	-1	μA
Gate-body leakage current	I _{GSS}	V _{GS} =±12V, V _{DS} = 0V	-	-	±100	nA
Gate threshold voltage	V _{GS(TH)}	V _{DS} =V _{GS} , I _D =-250μA	-0.5	-0.7	-1.0	V
Drain-source on-resistance	R _{DS(ON)}	V _{GS} =-4.5V, I _D =-2A	-	27	32	mΩ
		V _{GS} =-2.5V, I _D =-1.5A	-	38	45	
Diode Forward voltage _(note1)	V _{SD}	I _S =-5A, V _{GS} = 0V	-	-	-1.25	V
Dynamic characteristics						
Input Capacitance	C _{iss}	V _{DS} =-15V, V _{GS} =0V, f=1MHz	-	835	-	pF
Output Capacitance	C _{oss}		-	142	-	
Reverse Transfer Capacitance	C _{rss}		-	93	-	
Switching Characteristics						
Turn-on delay time	t _{d(on)}	V _{GS} =-4.5V, V _{DS} =-15V, R _L =5Ω, R _{GEN} =3Ω	-	12	-	nS
Turn-on rise time	t _r		-	30	-	
Turn-off delay time	t _{d(off)}		-	46	-	
Turn-off fall time	t _f		-	52	-	
Total Gate Charge	Q _g	V _{GS} =-4.5V, V _{DS} =-15V, I _D =-3A		8.9		nC
Gate Source Charge	Q _{gs}			1.5		
Gate Drain Charge	Q _{gd}			2.1		


Notes:

1. Repetitive rating; pulse width limited by maximum junction temperature.
2. EAS condition: $T_J = 25^{\circ}\text{C}, V_{DD} = -20V, V_G = 10V, R_g = 25\Omega, L = 0.5mH$.


Typical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise specified)




Drain Current vs. Drain-Source Voltage




Drain Current vs. Gate-Source Voltage




$R_{DS(on)}$ On-Resistance vs. Drain-Current



Capacitance vs. Drain-Source Voltage




Drain Current vs. Drain-Source Voltage




Normalized On-Resistance vs. Temperature

SOT23-3L Package Outline Drawing



SYM	MILLIMETERS		
	MIN	NOM	MAX
A	1.05	1.15	1.25
A1	0.01	0.06	0.11
A2	1.00	1.10	1.20
A3	0.60	0.65	0.70
b	0.35	0.40	0.45
c	0.12	0.15	0.18
D	2.82	2.92	3.02
E	2.65	2.80	2.95
E1	1.50	1.60	1.70
L	0.30	-	0.50
e	0.90	0.95	1.00
e1	1.80	1.90	2.00
θ	0°	4°	8°
L1	0.6REF		


Suggested Land Pattern




SYM	DIMENSIONS	
	MILLIMETERS	INCHES
C	2.20	0.087
E	0.95	0.037
E1	1.90	0.075
G	0.80	0.031
X	1.00	0.039
Y	1.40	0.055
Z	3.60	0.141

TAPE AND REEL INFORMATION


Reel Dimensions



Tape Dimensions



Unit:mm



IMPORTANT NOTICE

The information given in this document is believed to be accurate and reliable but shall in no event be regarded as a guarantee of conditions or characteristics. PN-Silicon assumes no responsibility for any errors in this document, or for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of PN-Silicon.

The product listed in this document are designed to be used with ordinary electronic equipment or devices and are not authorized to used with equipment or devices which require an extremely high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, aerospace machinery, nuclear-reactor controllers, automotive and other safety device.)

The  logo is a registered trademark of PN-Silicon co., ltd which reserves the right to make changes to the product or this document at any time without notice. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. PN-Silicon makes no warranty, representation or guarantee, express or implied, regarding the suitability of its products for any particular purpose. All rights reserved.